



DRAGON

130BBL Super Duty Non-Code Vacuum Tank Trailer



SPECIFICATIONS:

- 130 barrel non-code "Super Duty" vacuum trailer
- 5460 gallons, plus 2%
- 15 PSI internal, 22 INHG external, 23 PSIG hydrostatic test

OPTIONS:

- Self contained vacuum packages
- Ball float type with pointer located in rear tank head



VACTSDCAR130 • 9/14

tanktrailer.sales@modernusa.com • www.dragonproductsltd.com • 877-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.

130BBL Non-Code Vacuum Tanker

SPECIFICATIONS:

- Type: Vacuum tank trailer; non-DOT spec
- Capacity: 5460 gallons, plus 2%
- ICC MC: None
- Commodity: Unspecified oilfield fluids
- Design Pressure: 15 PSI Internal, 22 INHG external, 23 PSIG hydrostatic test
- Shell: 1/4" PL x 60" OD
- Baffle: (2) 1/4" PL flat flanged and dished each with interior shell reinforcement ring
- Stiffener: 3/8" x 2 1/2" rolled rings (8) external
- Welds: Internal root, external submerged-arc
- Compartment: Single
- Suspension: Hutch CH 9700 w/8 leaf low arch springs
- Axles: 22,500 LB round with outboard drums
- Wheels: 10 hole Steel Disc Hub Pilot
- Tires: 11.00 x 24.5 radials
- Brakes: 16-1/2" x 7" with spring parking, auto slacks, ABS both axles
- Upper Coupler: Bolt on adjustable
- Landing Legs: 2 speed, heavy duty, high capacity lift
- Bumper: 4" x 8" tube with tow eye
- Fenders: Full length formed hose pan (10 GA) with 1/4" formed supports
- Tool Box: 18" x 18" x 36" on driver's side with sealed door
- Mud Flaps: Anti sail
- Outlet: Two 4" butterfly valves at rear with a wedge sump
- Reliefs: 1-1/2" vacuum relief, 2" pressure relief, both located at top front of barrel, 2" blow down line at rear
- Manways: Four located on top, one on rear head, all 21" domed style with plated swing bolts and wing nuts
- Lights: Full DOT lights, sealed lights, harness and junction box with terminal strip, two rear work lights with integral switches
- Sight Glass: 2" sight glass fittings in front and rear head, 1-1/2" plastic sight glass tube installed in rear dead with clean out tees and 2" ball valves top and bottom
- Coating: All surfaces white metal steel grit blast, 2.5 ml profile (SP-10), Interior Lined with chemical resistant 100% solids epoxy liner, 10-15 ml dry film thickness. Exterior coated high build epoxy primer and color coated with high solids polyurethane, 4-6 ml dry film thickness



Optional Underbelly Self Contained Pump System



tanktrailer.sales@modernusa.com • www.dragonproductsltd.com • 877-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.