



Cooper SP400 Mobile Servicing Rig



SPECIFICATIONS:

- Service Depth: 14,500 ft (2-1/2" tubing)
- Workover Depth: 10,500 ft (2-7/8" DP)
- Max. static hook load: 205,000 lbs (6 lines)
- Clear Height, Mast: 96' Rated Horsepower, Engine: 350 HP/ 2,200 rpm
- Height, Tubing Board to ground: 55'-10"
- Height, Rod Board to ground: 78'-6"
- Carrier: 4 axle - two steer and two drive axles
- Diameter, Wireline: 1"
- Road Traveling dimensions: 56'-5" long x 9'-4" wide x 13'-8" high
- Carrier Dimensions (excluding mast): 38' long x 9'4" wide x 9'-8" high
- Maximum Speed: 55 mph Diesel Engine Specifications: (other options available)
- Traveling Weight: 75,000 lbs estimated (not including drill line, sand line, tools, block)
- Model: Caterpillar C9 ACERT Rated Horsepower: 350HP (2,200rpm)
- Maximum Torque: 1,148 lb.ft (1,400rpm)
- Transmission Specifications: (other options available)
- Axles: Four (two steer and two drive)
- Rating-Steering axles (two) 10 ton capacity (each)
- Drop Box to Right Angle Drive Gear Box
- Drop Box to Rear Drive Axles: Spicer 1710 dynamically balanced drive shaft
- Right Angle Gear Box Sand Drum: 1-3/4" double row chain
- Sand Drum Main Drum: 1-3/4" double row chain
- Drawworks System: Right Angle Drive (integrated torque tube)
- Ratio: 2.5:1 Dragon Products 96-205-6-T
- Mast: Certification: API 4F, 3rd Edition Clear Height: 96'
- Maximum static load: 205,000 lbs on 6-lines
- 180,000 lbs on 4-lines



rig.sales@modernusa.com www.dragonproductsltd.com 855-576-0682
U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.

COOP400 7/14