



Cooper SP650 Mobile Servicing Rig



SPECIFICATIONS:

- Drilling Depth: 8,500 ft (4 1/2" DP)
- Service Depth: 22,500 ft (2-7/8" DP)
- Workover Depth: 16,500 ft (3 1/2" DP)
- Max. static hook load: 350,000 lbs (8 lines)
- Mast clear height from ground: 112'
- Height, tubing board to ground: 70'-3" and 73'-6"
- Carrier: 6 axle - three steer, two drive axles, and one drag axle
- Diameter, wireline: 1 1/8"
- Road Traveling Dimensions:
65'-7 1/2" long x 12' wide x 15'-3" high
- Carrier dimensions (excluding mast):
51'-6" long x 11'-6" wide x 10' high
- Maximum speed: 55 mph
- Caterpillar C-18 700HP (2,100rpm) Industrial Diesel Engine
- Allison S6610 Straight thru Transmission
- Chelsea PTO mounted to the transmission supplies power to the main hydraulic
- TOTAL WEIGHT LESS LINE & TOOLS: 135,000#



COOP650 • 7/14

rig.sales@modernusa.com • www.dragonproductsltd.com • 855-576-0682

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.