



DRAGON

Roll-off Hoist Tag Trailer



SPECIFICATIONS:

GVWR: 40,000 Lb.

Trailer Main Frame Flanges:
1/2" X 5" A514 (T-1)

Trailer Main Frame Web Section:
1/4" A514 (T-1)

Hoist Frame:
4' X 8' X 1/2" Structural Tubing

Reeving Cylinder:
6' X 3' X 79' Interchangeable

Lift Cylinder:
6' X 3' X 79' Interchangeable

Turntable: Jost-Single Ball Bearing

Dump Angle:
Approximately 52 Degrees

Landing Gear: Hydraulic

Suspension: 48,000 Lb. Capacity,
8-Leaf Spring

Axles: Automatic Slack Adjusters,
Cast Hub and Drum, Hub Piloted,
5 In. Rd, 71 1/2' Track,
25,000 Lb. Capacity

Wheels: 8.25 x 24.5 Steel

Tires: 11Rx/22.5 (Low Profile)

Brakes: ABS Brake

Fenders: Stainless Steel

Electrical: DOT Lighting

Side Rollers: 4" O.D. Greasable
with SAE 660 Bronze Bushings

ICC Bumper: Automatic Fold Up

Ratchet Hold Downs: 2 Per Side

Toolbox: 30" Aluminum



tanktrailer.sales@modernusa.com • www.dragonproductsltd.com • 877-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.