




## LPG & NGL Skidded Storage Vessel



### SPECIFICATIONS:

- New manufactured tank - 18,000 & 30,000 gallon
- ASME Section VIII/Div 1 code compliant
- National board certified
- Buying direct from pressure vessel manufacturer
- Fully valved at factory and leak tested
- Load out station with integrated pump
- Prompt deliveries
- Severe duty engineered to consistently perform under punishing conditions



email: [production.equipment@modernusa.com](mailto:production.equipment@modernusa.com)

NGLRECOVTANK • 10/14

[www.dragonproductsltd.com](http://www.dragonproductsltd.com) • 800-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.

# LPG & NGL Skidded Storage Vessel

## GALLON STORAGE TANK WITH STEEL SADDLES 250 LB. WORKING PRESSURE

### COMPLETE NEW VALVE PACKAGE

- (2) 2" Internal Spring Reliefs w/ Break-Away Couplings, Stacks and Flappers
- (1) Visual Sight Gauge installed
- (1) ¾" Combo Valve at 85% level w/Vent Valve & Liquid filled #400psi pressure gauge
- (1) 3" Fisher 2 way Internal Valve rated 300gpm for liquid outtake for pump
- (2) 2" Fisher 2-way Internal Valves rated 250gpm: (1) for liquid in and (1) for Vapor Service
- All placards and signage are included with tanks to be installed after tank transport
- Hose Rack to protect hoses from ground exposure and tripping hazards

### NEW BULK HEAD WELDED TO SKID WITH VAPOR HOSE AND LIQUID FILL HOSE

- (1) 2' Snappy-Joe w/ Pneumatic Shut Down
- (1) 1 ¼" Snappy-Joe for Vapor Equalizing Connection between Truck and Tank
- (1) 2" Sight flow back check to visually confirm movement and unloading of product into Tank
- 14" Risers connected to Pneumatic System to provide System Shut Down in the event of pull away

### NEW 3 INCH PUMP WITH 10 HORSEPOWER 3-PHASE ELECTRIC MOTOR

### NEW SHUT DOWN SYSTEM

- Remote Safety Shut down Station located per NFPA 58, 2011
- Pneumatic system controls all internal valves

## OPERATED BY VAPOR PRESSURE, NITROGEN, OR CUSTOMER SUPPLIED PRESSURE SOURCE (DRY AIR, CO2)

- Truck loading / unloading ESV's (Provides protection at bulkhead)
- (1) 2' Snappy-Joe w/ Pneumatic Shut Down
- (1) 1 ¼" Snappy-Joe for Vapor Equalizing Connection between Truck and Tank
- (1) 2" Sight flow back check to visually confirm movement and unloading of product into Tank
- 14" Risers connected to Pneumatic System to provide System Shut Down in the event of pull away

### 2" VAPOR AND 2" LIQUID SERVICE VALVES

- (1) 2" LPG Rated Hose assembly w/ swivel, Valves and required ACME Fitting
- (1) 1 ¼" LPG rated Hose assembly w/ swivel, Valves and required ACME Fitting
- 2" Angle Valve w/ required ACME fitting w/ screen and sight flow back

### CUSTOMER OPTIONS:

- Blackmer 3" Pump, Motor, Base Assembly, 10HP 3-Phase motor w/ bypass. Approx 170gpm
- Blackmer 2" Pump, Motor, Base Assembly, 7 HP Single Phase Motor w/ bypass. Approx 70gpm
- Liquid Controls Meter 2" or 3" designed to customer specs
- Bulkhead can be configured on either side of the Tank
- Fitted with Openings and fitted with desired equipment at both ends
- Configured with or without pumps
- Tanks must and will be constructed to meet or exceed NFPA 58, 2011 code requirements



email: [production.equipment@modernusa.com](mailto:production.equipment@modernusa.com)

[www.dragonproductsltd.com](http://www.dragonproductsltd.com) • 800-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.