



DRAGON

Roll Off Hoist Units



SPECIFICATIONS:

- Overall length: 24' • Rail Length 22' - 3" • Rail Height 54"
- Capacity: 60,000 or 75,000 lbs.
- Container Lengths: 18' - 22'

OPTIONS:

- 30" Aluminum Toolbox
- Lengthen Truck Frame Tarp
- Pintle Hook, Air and Electrical Connections Wet Kit
- Hoist Up Alarm
- Customized Paint



tanktrailer.sales@modernusa.com • www.dragonproductsltd.com • 877-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.

ROH Mounted on Truck

- Capacity: 60,000 or 75,000 lbs.
- Tilt Frame: 8" x 4" x ½" Structural Tubing
Outside Rail Configuration: 35" O.D.
- Sub Frame: 4" x 2" x 3/16"
Structural Tubing
- Attached Hydraulic Plumbing
- Pump: Direct Mount 30 GPM
- PTO: Air Shift with Signal Light
Note: Hot Shift P.T.O. required on all automatic transmissions
- Controls: Inside and Outside Controls
- Lift Cylinder & Reeving Cylinder:
6" Bore x 3" Rod x 84" Stroke (60,000 lbs.) or
7" Bore x 3" Rod x 84" Stroke (70,000 lbs.)
Interchangeable Design
- Hydraulic Valve: VA-20 (40 GPM)
- Hydraulic Tank: Steel 50 Gallon
- Operating Pressure: 2,000 P.S.I. Max.
- Dump Angle: 49 deg.
- Cable: 7/8" Dia. EXIWRC 6 x 37 1" dia. X 8"
Weldless Alloy Link End
- Rear Fenders: Stainless Steel or Poly
- Side Rollers: 4" O.D. Greasable with SAE
660 Bronze Bushings (5) per side
- Bumper: Automatic Fold-Up ICC Bumper
- Available as a "Ship-Out" complete unit or
Factory Installed at one of our locations.
- Cab to axle space required=184"

Optional:

- 30" Aluminum Toolbox
- Lengthen Truck Frame Tarper
- Pintle Hook, Air and Electrical Connections Wet Kit
- Hoist Up Alarm
- Customized Paint

