



DRAGON[®]

Single Container Trailers



SPECIFICATIONS:

- Overall length: 34' • Rail Length 31'- 3" • Rail Height 60"
- G.V.W.R: 72,000 lb. +
- Container Lengths: 18' - 30'
- 7" Bore x 3" Rod x 120" Stroke Reeving Cylinder
- 6 Bore x 118" Stroke x 3 Stage Lift Cylinder
- 7/8" Cable EXIWRC 6 x 36



tanktrailer.sales@modernusa.com • www.dragonproductsltd.com • 877-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.

(SCT) Single Container Trailers

SPECIFICATIONS:

- **G.V.W.R:** 72,000 lb.
- **Rail Configuration:** Outside Roller 35" Outside
- **Container Lengths:** 18' - 30'
- **Trailer Main Frame:** Fabricated I-Beam
- **Flanges:** 5/8" T1 Steel; Web: 1/4" T1 Steel
- **Tilt Frame:**
Structural Tubing: 10" x 4" x 1/2"
- **Lift Cylinders:** 6" Bore x 118" Stroke x 3
Stage - Double Acting Telescopic
- **Reeving Cylinders** - 7" Bore x 3" Rod x 120" stroke
- **Hydraulic Valve:** 2 Spool - 35 GPM with Pressure Relief
- **Operating Pressure:** 2,000 PSI Maximum
- **Dump Angle:** 47 Degrees
- **Landing Gear:** 2 Speed - 50,000 lb. Capacity
- **ICC Bumper:** Automatic Fold-Up - Air Actuated
- **Side Rollers:** 4" O.D. (6) per Side
- **Ratchet Hold Downs:** (2) per Side
- **Rear Fenders:** Stainless Steel
- **Toolbox:** 30" Aluminum with Step
- **Suspension:** Watson & Chalin
(Air Ride Model: TA-302-15) 15" Ride Height
30,000 lb. each
- **Axles:** Automatic slack adjusters, Outboard Drum 5" round 71 1/2"
track 25,000 lb. Hub piloted tandem.
- **Wheels:** Steel 8.25 x 24.5
- **Tires:** 11R24.5 14 Radial Ply
- **Brakes:** ABS (Wabco 2S1M System)
- **DOT Approved Lights**

OPTIONS:

- Axle Lift
- Tri Axle with Axle Lift
- Tarp System



tanktrailer.sales@modernusa.com • www.dragonproductsltd.com • 877-231-8198

U.S. owned and operated for over 50 years. © Copyright 2014 Modern Group Inc. All rights reserved.